



TECNOSUB



Hydraulic Power Pack

PLARAD
Torque & Tension Systems



Hydraulic Power Pack with Electric Motor - PLARAD IQ-VAX

Dimensions:

L x W x H (cm): 570 x 275 x 420
Weight: 22 KGR (with liquids)

Electric Characteristics:

230 V - 2 Phase - 50/60 Hz

Hydraulic Characteristics:

Flow Rate: 5,3 to 0,75 l/min
Pressure: Up to 800 bar

Features:

Continuous manual adjustment of pressure over the whole range
The high-speed cooling from the start of work guarantees permanent operation
Plarad VX compensates for fluctuations of up to 20% of the nominal voltage
An ergonomically outstanding decibel reduction makes the power pack extremely quiet
Can be upgraded with additional oil tanks, e.g. when using several tools
Solid frame construction for the protection of the power pack suitable for on-site use

TECNOSUB'S HEADQUARTERS

c/ Pau del Protectorat, 18
43004 - Tarragona (SPAIN)
Tel: +34 977 252 802 Fax: +34 977 237 551
www.tecnosub.net
E-mail: spain@tecnosub.net





TECNOSUB



Hydraulic Torque Wrench

PLARAD
Torque & Tension Systems



Hydraulic Torque Wrench - PLARAD MSX T 45 TS

Dimensions:

L x W x H (mm): 212 x 67 x 122

Weight: 4,9 KGR

Square Drive: 1"

Hydraulic Characteristics:

Performance Range: 450 - 4500 Nm

Pressure: Up to 800 bar

Features:

360° rotatable reaction arm

Reinforced release shock absorber

Patented high pressure safety cylinder

Housing of high-strength alloy

Suitable for all industrial requirements

For hexagonal (Allen) sockets, standard and safety nuts

Also available for use in hazardous areas for zone I (gas), according to ATEX standard.

TECNOSUB'S HEADQUARTERS

c/ Pau del Protectorat, 18

43004 - Tarragona (SPAIN)

Tel: +34 977 252 802 Fax: +34 977 237 551

www.tecnosub.net

E-mail: spain@tecnosub.net





TECNOSUB



Hydraulic Torque Wrench

PLARAD
Torque & Tension Systems



Hydraulic Torque Wrench - PLARAD MSX T 75 TS

Dimensions:

L x W x H (mm): 253 x 80 x 139

Weight: 7,3 KGR

Square Drive: 1- 1/2"

Hydraulic Characteristics:

Performance Range: 750 - 7500 Nm

Pressure: Up to 800 bar

Features:

360° rotatable reaction arm

Reinforced release shock absorber

Patented high pressure safety cylinder

Housing of high-strength alloy

Suitable for all industrial requirements

For hexagonal (Allen) sockets, standard and safety nuts

Also available for use in hazardous areas for zone I (gas), according to ATEX standard.

TECNOSUB'S HEADQUARTERS

c/ Pau del Protectorat, 18

43004 - Tarragona (SPAIN)

Tel: +34 977 252 802 Fax: +34 977 237 551

www.tecnosub.net

E-mail: spain@tecnosub.net





TECNOSUB



Hydraulic Torque Wrench

PLARAD
Torque & Tension Systems



Hydraulic Torque Wrench - PLARAD MSX T 250 TS

Dimensions:
L x W x H (mm): 290 x 118 x 229
Weight: 29,5 KGR
Square Drive: 2- 1/2"

Hydraulic Characteristics:
Performance Range: 2500 - 25000 Nm
Pressure: Up to 800 bar

Features:
360° rotatable reaction arm
Reinforced release shock absorber
Patented high pressure safety cylinder
Housing of high-strength alloy
Suitable for all industrial requirements
For hexagonal (Allen) sockets, standard and safety nuts
Also available for use in hazardous areas for zone I (gas), according to ATEX standard.

TECNOSUB'S HEADQUARTERS

c/ Pau del Protectorat, 18
43004 - Tarragona (SPAIN)
Tel: +34 977 252 802 Fax: +34 977 237 551
www.tecnosub.net
E-mail: spain@tecnosub.net

